

PANTUM

The New Era for Printing

Reliability is all that matters.

Sick of filling up the paper tray or changing toners? New Pantum high speed automatic duplex P3500 series offers massive paper input up to 1410 pages. This robust machine delivers efficient and reliable printing experience you require for your business.

P3500 Series
Monochrome Laser Printer



Print **12** basketball courts monthly
1.5 basketball courts all at once



Fast Print Speeds



**Wi-Fi Connectivity
and Mobile Printing**



**550 Sheet X2
Optional Paper Tray**



**Convenient One
Step Installation**



**80000 Page
Monthly Duty Cycle**

PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS



P3500 Series

Available in ■ Black

Models

P3500DN

P3500DW

Printing

Print Technology	Mono laser	
Print speed	33ppm (A4) / 35ppm (Letter)	
First print out time	Less than 8.5 seconds	
Max. monthly volume	80000 pages	
Recommended monthly volume	5000 pages	
Processor speed	600MHz	
Memory	256MB	
Resolution(dpi)	1200x1200dpi (Max)	
Printer language	PCL5e, PCL6/XL, PS3, PDF	
Duplex Mode	Auto	
Network	Yes	
Wi-Fi	No	Yes

Paper handling

Paper Input tray	250 pages	
Multipurpose tray	60 pages	
Optional tray	Yes (550*2 pages)	
Paper Output tray	150 pages	
Media types	Multipurpose tray: Plain, Thick(Tough), Thin, Transparency, Cardstock, Label, Envelope Standard tray: Plain, Thin Optional tray: Plain, Thin	
Media sizes	A4, A5, A5L A6, JIS B5, ISO B5, B6, Letter, Legal, Executive, Folio, Oficio, Statement, 16K, Big 16K, 32K, Big 32K, No.10 Env., Monarch Env, DL Env, C5 Env, C6 Env, ZL, Japanese Postcard, custom; Yougata4, Younaga3, Nagagata3, Yougata2	
Media Weight	Multipurpose tray: 60~200 g/m ² ; Standard tray: 60~105 g/m ² Optional tray 60-105g/m ²	

General

Dimensions (wxdxh)	370x370x286mm (14.6"*14.6"*11.3")	
Display	2line LCD	
Weight (without toner cartridge)	9.4kg (20.7lb)	
Operating temperature range	Recommended temperature: 10-35 °C (10-95 °F)	
Operating humidity range	Humidity range: 20% - 80%	
Input voltage	110V Model: AC100~127V, 50Hz/60Hz; 8A 220V Model: AC220~240V, 50Hz/60Hz; 4A	
Power consumption	Printing: 470W Ready: 50W Sleep: Less than 2.5W	
Operating system compatibility	Microsoft Windows Server2003/Server2008/Server2012/XP/Vista/Win7/Win8/Win8.1/Win10(32/64 Bit) Mac OS X 10.6/10.7/10.8/10.9/10.10/10.11 Linux (ubuntu 12.04/14.04)	
Connectivity	HI-SPEED USB2.0; Net: IEEE 802.3 10/100/1000Base-TX;	HI-SPEED USB2.0; Net: IEEE 802.3 10/100/1000Base-TX; WiFi: IEEE 802.11b/g/n;
Energy efficiency	ENERGY STAR® 2.0 Certified	

Consumable

Toner cartridge ⁽¹⁾	P*-310 Series Standard capacity toner P*-310(3,000 pages), High capacity toner P*-310H(6,000 pages)	
--------------------------------	--	--

What's in the box

Printer×1/3,000 Page Toner Cartridge×1/USB Interface Cable×1/
Power Cord×1/CD-ROM×1/Quick Setup Guide×1

(1) Average yield per toner cartridge in accordance with ISO/IEC 19752 (Individual users will experience different results based on their environment and page coverage)

Copyright ©2016 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.